



Innovators of Freight Securement Systems®

Loadbar Wide®

The next generation one-way loadbar solution for securing light to medium weight loads.

Installation Guide



The complete Installation Guide for Logistick's Loadbar Wide®.


For best results, please read through all instructions prior to installation.

Materials Needed

- Loadbar Wide®
- 96 Inch 2x4
- Dry Cloth
- Scraper (optional)
- Rubbing Alcohol (optional)
- Saw (optional)

1. Choosing the Application Area


After loading the cargo, determine the best location for installation. Keep in mind that multiple sets of Loadbar Wide® may be needed to safely secure your cargo. Choose an area that will place the Loadbar Wide® at the same height and position, assuring the 2x4 will be installed parallel to the floor. The 2x4 needs to be against the freight, which will prevent the cargo from starting to shift.



IMPORTANT: Once Loadbar Wide® is installed, it cannot be repositioned.

2. Prepping the Application Area

The entire application area must be clean and dry to ensure proper installation. Use a dry cloth, and if needed, a scraper and rubbing alcohol to remove loose dirt, dust, condensation or frost from the application area.







3. Preparing for Installation

To ensure proper fit and pressure, always use a standard 96 inch (8 foot) 2x4. Each Loadbar Wide® contains a perforated foam insert that is engineered to apply continuous pressure between the 2x4 and the walls of the trailer. **The Loadbar Wide® is specifically designed for use in wide trailers with an inside width of 99 to 102 inches.** If the inside width of the trailer is less than 99 inches, cut your 2x4 to 4 inches **less than the inside width of the trailer at the application area.**

4. Installation




Remove the tape backing from ONE Loadbar Wide®. In a level manner, place the Loadbar Wide® onto the determined application area of one wall - **making sure that the handle is pointed away from the freight and the pocket of the Loadbar Wide® is positioned so the 2x4 will be in contact with the freight.** Next, insert the 2x4 into the pocket of the installed Loadbar Wide® and place the second Loadbar Wide® onto the opposite end of the 2x4 in the same orientation as the first. **With the tape backing still in place,** pull the second Loadbar Wide® towards you and slide into the chosen application area on the opposite wall of the trailer until the 2x4 is level and snug against the cargo. An ample amount of force is needed to slide the second Loadbar Wide® into place because of the outward pressure of the system. **If the pressure is too great, remove half of ONE foam insert and try to re-install.** If the pressure is still too much, remove half of the foam insert from the opposite side and re-install. **Never remove all foam from either Loadbar Wide®.**



5. Removal of the Tape Backing from Second Loadbar Wide®


Once the second Loadbar Wide® is in position, locate the exposed white adhesive tab near the handle. Fold adhesive tab against the Loadbar Wide® and peel back the corner of the tape backing for easy grasp.

While carefully maintaining the position of the 2x4 and second Loadbar Wide®, use one hand to pull the handle of the Loadbar Wide® slightly toward you and away from trailer wall. With your other hand, grab the corner of the tape backing. Pull down and toward the rear of the Loadbar Wide®, exposing several inches of the adhesive. Next, slowly release the handle and gently secure the exposed portion of adhesive to the trailer wall. Once secure, hold the Loadbar Wide® in place with one hand and pull the remaining portion of the backing downward and toward the rear of the Loadbar Wide®. Make sure the entire tape backing is removed so the adhesive surface is uncovered and exposed to the wall.



6. Securing the Loadbar Wide®

When the entire tape backing has been removed from the second Loadbar Wide®, press it firmly and squarely against the wall. Repeat this action with the other Loadbar Wide®, making sure firm and steady pressure is applied. Continue this process until you feel certain the entire surface of each Loadbar Wide® has fully adhered to the wall.



Logistick.com

If you have any questions about this product or any
of our other products please email us at
sales@logistick.com

**Thank you for your business and
continued partnership.**



Scan for full video!



Innovators of Freight Securement Systems®

Revised October 2022
L.21



Innovators of Freight Securement Systems®

Loadbar Wide®

The next generation one-way loadbar solution for securing light to medium weight loads.

Removal Guide



The complete Removal Guide for Logistick's Loadbar Wide®.




Materials Needed

- Safety Knife
- Prybar
- Cloth (optional)
- Scraper (optional)
- Citrus Based Adhesive Remover (optional)

1. Removal of the 2x4


One side of each Loadbar Wide® pocket has scoring channels. Since each Loadbar Wide® is designed for either right or left side use, scoring channels will be accessible on at least one Loadbar Wide®. Score these channels thoroughly with a safety knife. Next, break open and bend back the top of the Loadbar Wide® pocket using a prybar, so the 2x4 is exposed. Lift and remove the 2x4 from the pocket by prying and pulling up.

Optional: Use a forklift to slowly lift one side of the 2x4 near a Loadbar pocket, releasing the Loadbar from the wall. **Use caution to not damage freight.**



2. Removal of the Loadbar Wide®

Remove each Loadbar Wide® by pulling the handle downward and away from the wall while sliding a prybar down between the Loadbar Wide® and the wall of the trailer. Use slow and steady outward pressure to pry and pull Loadbar Wide® off the wall.



3. Removing Tape Remnants

Use a cloth, and if needed, a scraper and a citrus based adhesive remover to clean any remaining tape residue from the trailer walls.



Scan for full video!



Innovators of Freight Securement Systems®

Revised October 2022
L.21